

- + Polyamide hand held enclosure for MCR- and automation engineering
- + Version with or without display opening
- + Prepared for acceptance of keypads/silicone switch mats
- + Optional EMC version with internal coating and EMC-seal

### Included in delivery

Double-skinned enclosure with top and base unit, each with fixing domes, fastening and enclosure screws.

## Technical data

Material:	Polyamide
Colour:	RAL 7021, schwarzgrau
Ingress protection:	IP 65 to EN 60529
Flammability:	UL 94 V-2
Surface resistance:	$10^{12}$ Ohm to IEC 60093
Temperature range:	-40°C to +60°C

## Product range

Product type	Order number	Dimensions H x W x D (mm)
Beluga 180 O	27.02 02 00	106/75 x 187 x 50

## Accessories

### Battery box empty

Order number

**27.02 00 85**

### Display fixing set

Order number

**27.01 06 80**

### Membrane keypads

Order number

Description of accessories

**82.10 00 03**

FT 180 b, 15 keys, printed, Matrix

**82.10 00 04**

FT 180 e, 15 keys, with paper strap, Matrix

**82.10 00 07**

FT 180 ge, 12 Tasten,with paper strap, common connection

### Spare screw set

Order number

**27.02 00 82**

### Battery holder

Order number

Description of accessories

**27.02 00 86**

for 4 micro-cells (AAA)

**27.02 00 87**

for 9 V monoblock

### Hook set

Order number

Description of accessories

**27.02 00 80**

without magnet for B 180/220

**27.02 00 81**

with magnet for B 180/220

### Cable connection with bending protection (no lock nut)

Order number

Description of accessories

**08.10 01 16**

M16 x 1,5

### Hand strap

Order number

Description of accessories

**27.02 00 83**

hand strap Beluga 180/220

### connector

Order number

**82.20 00 08**

### Wall holder

Order number

Description of accessories

**27.02 00 84**

for hook set

### Enabling switch

Order number

Description of accessories

**83.50 00 10**

2-step, 1NC, blue

## Certificates

No approvals