

## Ex empty

- + Hand held enclosures as empty enclosures for Ex-applications
- + 3 enclosure sizes
- + Optional version with display openings

### Included in delivery

Enclosure system consisting of top and base with seal.  
O version = open: with display screen and mounting material for window

### Technical data

<b>Explosion protection:</b>	II 2G Ex e IIC Gb II 2D Ex tb IIIC Db
<b>Material:</b>	Polyamide 12
<b>Certificates:</b>	IECEX PTB 09.0019U, PTB 02 ATEX 1076U
<b>Colour:</b>	RAL 9005, tiefschwarz
<b>Ingress protection:</b>	IP 65 to EN 60529
<b>Impact resistance:</b>	7 Joule to EN 60079-0
<b>Flammability:</b>	UL 94 HB
<b>Surface resistance:</b>	<math>10^9</math> Ohm to IEC 60093
<b>Temperature range:</b>	-20°C bis +60°C
<b>Other versions on request:</b>	EMC

### Product range

Product type	Order number	Dimensions H x W x D (mm)
Beluga 380 ExB	<b>28.02 05 01</b>	380 x 117 x 68

## Accessories

### Carrying strap

Order number	Description of accessories
<b>27.02 05 80</b>	carrying strap Beluga 380

### Wall holder

Order number
<b>27.02 05 82</b>

## Certificates

ATEX

IECEX

CCOE India

EAC (TR CU)