

- + Polyamide hand held enclosure for MCR- and automation engineering
- + Version with or without display opening
- + Prepared for acceptance of keypads/silicone switch mats
- + Optional EMC version with internal coating and EMC-seal

Included in delivery

Double-skinned enclosure with top and base unit, each with fixing domes, fastening and enclosure screws.

Technical data

Material:	Polyamide
Colour:	RAL 7021, schwarzgrau
Ingress protection:	IP 65 to EN 60529
Flammability:	UL 94 V-2
Surface resistance:	10^{12} Ohm to IEC 60093
Temperature range:	-40°C to +60°C

Product range

Product type	Order number	Dimensions H x W x D (mm)
Beluga 220 O	27.02 04 00	116/85 x 220 x 51

Accessories

Battery box empty

Order number

27.02 00 85

Membrane keypads

Order number

Description of accessories

82.10 00 05

FT 220 b, 18 keys, printed, Matrix

82.10 00 06

FT 220 e, 18 keys, with paper strap, Matrix

Spare screw set

Order number

27.02 00 82

Battery holder

Order number

Description of accessories

27.02 00 86

for 4 micro-cells (AAA)

27.02 00 87

for 9 V monoblock

Hook set

Order number

Description of accessories

27.02 00 80

without magnet for B 180/220

27.02 00 81

with magnet for B 180/220

spare display screen

Order number

27.02 04 83

Cable connection with bending protection (no lock nut)

Order number

Description of accessories

08.10 01 20

M20 x 1,5

Hand strap

Order number

Description of accessories

27.02 00 83

hand strap Beluga 180/220

connector

Order number

82.20 00 09

Wall holder

Order number

Description of accessories

27.02 00 84

for hook set

Enabling switch

Order number

Description of accessories

83.50 00 10

2-step, 1NC, blue

Certificates

No approvals