

Beluga 220

- + Polyamide hand held enclosure for MCR- and automation engineering
- + Version with or without display opening
- + Prepared for acceptance of keypads/silicone switch mats
- + Optional EMC version with internal coating and EMC-seal

Included in delivery

Double-skinned enclosure with top and base unit, each with fixing domes, fastening and enclosure screws.

Technical data

Material:	Polyamide
Colour:	RAL 7021, schwarzgrau
Ingress protection:	IP 65 to EN 60529
Flammability:	UL 94 V-2
Surface resistance:	10^{12} Ohm to IEC 60093
Temperature range:	-40°C to +60°C

Product range

Product type	Order number	Dimensions H x W x D (mm)
Beluga 220 G	27.02 04 01	116/85 x 220 x 51

Accessories

Battery box empty

Order number

27.02 00 85

Spare screw set

Order number

27.02 00 82

Battery holder

Order number

Description of accessories

27.02 00 86

for 4 micro-cells (AAA)

27.02 00 87

for 9 V monoblock

Hook set

Order number

Description of accessories

27.02 00 80

without magnet for B 180/220

27.02 00 81

with magnet for B 180/220

Cable connection with bending protection (no lock nut)

Order number

Description of accessories

08.10 01 20

M20 x 1,5

Hand strap

Order number

Description of accessories

27.02 00 83

hand strap Beluga 180/220

Wall holder

Order number

Description of accessories

27.02 00 84

for hook set

Enabling switch

Order number

Description of accessories

83.50 00 10

2-step, 1NC, blue

Certificates

No approvals