

Ex empty

- + Hand held enclosures as empty enclosures for Ex-applications
- + 3 enclosure sizes
- + Optional version with display openings

Included in delivery

Enclosure system consisting of top and base with seal.
O version = open: with display screen and mounting material for window

Technical data

Explosion protection:	II 2G Ex e IIC Gb II 2D Ex tb IIIC Db
Material:	Polyamide 12
Certificates:	IECEX PTB 09.0019U, PTB 02 ATEX 1076U
Colour:	RAL 9005, tiefschwarz
Ingress protection:	IP 65 to EN 60529
Impact resistance:	7 Joule to EN 60079-0
Flammability:	UL 94 HB
Surface resistance:	10^9 Ohm to IEC 60093
Temperature range:	-20°C bis +60°C
Other versions on request:	EMC

Product range

Product type	Order number	Dimensions H x W x D (mm)
Beluga 180 O ExB	28.02 02 00	106/75 x 187 x 50

Accessories

Spare display screen

Order number

28.99 00 01

Hook set

Order number

Description of accessories

27.02 00 80

without magnet for B 180/220

Hand strap

Order number

Description of accessories

27.02 00 83

hand strap Beluga 180/220

Certificates

ATEX

IECEX

CCOE India

EAC (TR CU)